

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 to 19 (cancelled).

20. (original) An irrigation tip for use in a body joint, the tip being used with a handpiece and comprising:

a shaft forming an irrigation lumen and having an outer surface, the shaft being

connectible to the handpiece; and

a debrider for debriding an interior surface of the body joint, the debrider being connected to the shaft and defining a substantially planar debriding surface.

21 to 27 (cancelled).

29. (amended) An arthroscopically insertable device for arthroscopic therapeutic treatment of a joint to remove irritants fragments from the joint comprising:

a shaft having a proximal end and a distal end, the shaft being relatively rigid for most of its length;

a debridement tip mounted to the distal end of the shaft, the debridement tip being more flexible than the relatively rigid portion of the shaft and having a flexible debridement surface;

the rigidity of the shaft being sufficient to enable manipulation of the shaft to bring the debridement tip to bear forcefully against selected internal regions of a joint;

the debridement tip and debridement surface having sufficient abrasion characteristics to enable arthroscopic debridement of irritant fragments from selected regions of a joint and being sufficiently resilient and flexible as to forcefully debride said regions with ~~reduced~~ minimized trauma.

30. (amended) A device as defined in claim 29 further comprising a lumen

extending through the shaft and communicating with at least one emission outlet ~~emission~~ in the debridement tip, the outlet and lumen enabling emission of pressurized liquid streams at a sufficient velocity and impact force to facilitate debridement.

31. (previously presented) An arthroscopically insertable device as defined in claim 30 further comprising a plurality of said emission outlets.

32. (amended) An arthroscopically insertable device as defined in claim 31 wherein at least one of said emission outlets is oriented to direct emitted liquid in a generally distal direction and at least one of the emission outlets is oriented to direct emitted liquid in a radial direction.

33. (previously presented) A device as defined in claim 29 further comprising:
the debridement tip being molded from a polymer to include a portion having a cross-sectional dimension that is smaller than the cross-sectional dimension of the shaft; and

a plurality of bristles protruding laterally from said surface of the debridement tip, the outer ends of the bristles defining the debridement surface, the ends of the bristles extending not substantially beyond the cross-sectional dimension of the shaft whereby the cross-sectional profile of the debridement tip and the shaft are of sufficiently small cross-sectional dimensions to enable arthroscopic insertion of the tip into a joint.

34. (previously presented) An arthroscopically insertable device as defined in claim 33 further comprising at least one emission outlet in the debridement tip that is disposed between the most proximal and most distal of the bristles and is oriented to direct an emitted stream in a radial direction.

35. (previously presented) A device as defined in claim 33 wherein the bristles are molded integrally with the tip.

36. (previously presented) A device as defined in claim 33 further comprising:
the tip being molded to include an internal chamber that communicates with the lumen, the outlets being formed in the tip to communicate with the chamber.

37. (amended) An arthroscopically insertable device for arthroscopic therapeutic treatment of a joint to remove irritants from the joint ~~a device as defined in claim 36 further comprising:~~

an arthroscopically insertable device for arthroscopic therapeutic treatment of a joint to remove irritants from the joint comprising:

a shaft having a proximal end and a distal end, the shaft being relatively rigid for most of its length;

a debridement tip mounted to the distal end of the shaft, the debridement tip being more flexible than the relatively rigid portion of the shaft and having a flexible debridement surface;

the rigidity of the shaft being sufficient to enable manipulation of the shaft to bring the debridement tip to bear against selected internal regions of a joint;

the debridement tip and debridement surface having sufficient abrasion characteristics to enable arthroscopic debridement of selected regions of a joint and being sufficiently resilient and flexible as to debride said regions with reduced trauma.

the debridement tip being molded from a polymer to include a portion having a cross-sectional dimension that is smaller than the cross-sectional dimension of the shaft; and

a plurality of bristles protruding laterally from said surface of the debridement tip, the outer ends of the bristles defining the debridement surface, the ends of the bristles extending not substantially beyond the cross-sectional dimension of the shaft whereby the cross-sectional profile of the debridement tip and the shaft are of sufficiently small cross-sectional dimensions to enable arthroscopic insertion of the tip into a joint.

the tip being molded to include an internal chamber that communicates with the lumen, the outlets being formed in the tip to communicate with the chamber;

the shaft having a reduced diameter at its distal end, the proximal end of the tip defining a socket receptive to the reduced diameter distal tip of the shaft, the outer dimensions of the proximal end of the tip and the distal end of the shaft being substantially the same to define a relatively smooth transition between the external surfaces of the shaft and the tip.

38. (previously presented) A device as defined in claim 37 further comprising:
at least one stiffening finger extending from the distal end of the shaft, the finger being contained within the chamber and being dimensioned and formed to control the degree of flexibility for the distal portion of the debridement tip.

39. (amended) An arthroscopically insertable device for arthroscopic therapeutic treatment of a joint to remove irritants from the joint comprising:

A device as defined in claim 33

an arthroscopically insertable device for arthroscopic therapeutic treatment of a joint to remove irritant fragments from the joint comprising:

a shaft having a proximal end and a distal end, the shaft being relatively rigid for most of its length;

a debridement tip mounted to the distal end of the shaft, the debridement tip being more flexible than the relatively rigid portion of the shaft and having a flexible debridement surface;

the rigidity of the shaft being sufficient to enable manipulation of the shaft to bring the debridement tip to bear forcefully against selected internal regions of a joint;

the debridement tip and debridement surface having sufficient abrasion characteristics to enable arthroscopic debridement of irritant fragments from selected regions of a joint and being sufficiently resilient and flexible as to forcefully debride said regions with minimized trauma.

the debridement tip being molded from a polymer to include a portion having a cross-sectional dimension that is smaller than the cross-sectional dimension of the shaft; and

a plurality of bristles protruding laterally from said surface of the debridement tip, the outer ends of the bristles defining the debridement surface, the ends of the bristles extending not substantially beyond the cross-sectional dimension of the shaft whereby the cross-sectional profile of the debridement tip and the shaft are of sufficiently small cross-sectional dimensions to enable arthroscopic insertion of the tip into a joint;

wherein the tip has a pair of flat sides with the bristles extending from each of the flat sides, the flat sides defining a thin portion of the tip adapted for insertion into small crevices.

40. (previously presented) A device as defined in claim 33 further comprising:
the bristles extending from at least one surface of the tip that is disposed radially inwardly of the more proximal portion of the tip.

41. (previously presented) An arthroscopically insertable device as defined in claim 29 wherein the shaft has an outer sleeve formed integrally with and from the same material as the debrider and a stiffening tube is disposed within the sleeve.

42. (previously presented) An arthroscopically insertable device as defined in claim 29 wherein the debriding surface does not extend substantially beyond the radial dimensions defined by the shaft.

43. (previously presented) An arthroscopically insertable device as defined in claim 42 further comprising the debrider having a recessed surface from which the bristles extend.

44. (previously presented) An arthroscopically insertable device as defined in claim 42 wherein the debriding surface of the debrider does not extend radially beyond the transverse cross-sectional dimension of the shaft more than about 0.16 inch.

45. (previously presented) An arthroscopically insertable device as defined in

claim 44 wherein the shaft has a maximum outer diameter of approximately 0.35 inch.

46. (previously presented) An arthroscopically insertable device as defined in claim 29 further comprising a knob mounted to the shaft, the connector being constructed to be rotatable with respect to the handpiece whereby manipulation of the knob may enable orientation of the emission outlet and the debrider to be changed without changing the orientation of the handpiece.

47. (previously presented) An arthroscopically insertable device as defined in claim 29 wherein the juncture of the debrider and the shaft is substantially smooth to facilitate entry and removal of the tip from the joint.